



SPOUTING							
	MATERIAL					CAPACITY	
SPOUTING PROFILE	COPPER	COLORCOTE (ZR8)	ZRX	ZINC	ALUMINIUM (ARX)	DISTANCE OUT FROM FASCIA	CROSS SECTION mm2
125mm O/G	✓	✓	✓	✓	✓	125mm	5800
1/4 ROUND	✓	✓	✓	✓	✓	135mm	6300
150mm O/G	✓	✓	✓			150mm	9000
BOX GUTTER	✓	✓	✓			125mm	7500
1/2 ROUND	✓	✓	✓	✓	✓	150mm	8700
THE TEXAN	✓	✓	✓		✓	175mm	20100

	BRACKETS					DOWNPIPES			
	MATERIAL				POSITIONING		DIAMETER OPTIONS		
SPOUTING PROFILE	BRASS	COPPER	GALV	ALUMINIUM	INTERNAL BRACKETS	EXTERNAL BRACKETS	65mm	80mm	100mm
125mm O/G	✓	✓	✓	✓	✓	✓	✓	✓	
1/4 ROUND	✓	✓	✓	✓	✓	✓	✓	✓	✓
150mm O/G	✓	✓	✓	✓	✓	✓	✓	✓	✓
BOX GUTTER	✓	✓	✓	✓	✓	✓	✓	✓	✓
1/2 ROUND	✓	✓	✓	✓		✓	✓	✓	✓
THE TEXAN	✓	✓	✓			✓	✓	✓	✓

DOWNPIPES									
	MATERIAL					MAX ROOF AREA PER DOWNPIPE			
DOWNPIPE SIZE	COPPER	ZINCALUME	COLORCOTE (ZR8)	ZRX	ALUMINIUM (ARX)	ROOF PITCH (degrees)			
						0 - 25	26 - 35	36 - 45	46 - 55
65mm ROUND	✓	✓	✓	✓	✓	60	50	40	35
80 mm ROUND	✓	✓	✓	✓	✓	100	80	70	60
100 mm ROUND	✓	✓	✓	✓		155	130	110	90